



Kilsaran

KPRO
FLOOR

Introducing our New LevelEase Range Your Complete Flooring Solution



LevelEase 250

A rapid hardening and fibre reinforced cementitious levelling compound for use in domestic and commercial applications, over a multitude of substrate. Laying depth 2mm-50mm. CT-C30-F7.



LevelEase 225

A standard-setting and fibre-reinforced cementitious levelling compound for use in domestic and commercial applications. Laying depth 2mm-25mm. CT-C25-F6.



LevelEase Duo 225

A standard-setting two component cementitious levelling compound for use in domestic and commercial applications. Laying depth 2mm-25mm. CT-C25-F6.



LevelEase Sealing Primer

A high-performance, deep-penetrating primer designed to strengthen absorbent substrates and improve adhesion for subsequent layers. It ensures reduced absorbency and enhanced workability for a wide range of surface preparation tasks.



LevelEase Gritty Primer

A quartz infused, high-performance and fast-setting bonding primer which delivers a textured, gritty finish that significantly enhances the adhesion of subsequent layers, to smooth non-absorbent substrates.



LevelEase DPM

A one-component, water-based residual moisture vapor suppressant, designed to suppress residual construction moisture in cementitious substrates, where the moisture content is up to 95% RH.

Get in touch:

ROI: T: 01 801 3484 www.kilsaran.ie | **UK:** T: 0161 872 8899 www.kilsaraninternational.co.uk

Place an Order: orders@kilsaran.ie **Customer Service:** csteam@kilsaran.ie

Tech Support: techsupport@kilsaran.ie





Kilsaran

KPRO FLOOR



| Laying Dept | | LevelEase 250 | LevelEase 225 | LevelEase Duo 225 |
|---------------------------------|--------------------------|---|---|---|
| | | 2mm – 50mm | 2mm – 25mm | 2mm – 25mm |
| Suitability of substrates | Concrete | ... | .. | .. |
| | Plywood* | ... | o | o |
| | S&C Screed | ... | .. | .. |
| | Calcium Sulphate Screed | ... | .. | .. |
| | Ceramic Tiles | ... | .. | .. |
| Substrate preparation | LevelEase Sealing Primer | Required | Required | Required |
| | LevelEase Gritty Primer | Required on tiled substrates | Required on tiled substrates | Required on tiled substrates |
| | LevelEase DPM | If substrate moisture is $\geq 75\%$ RH, $\leq 95\%$ RH | If substrate moisture is $\geq 75\%$ RH, $\leq 95\%$ RH | If substrate moisture is $\geq 75\%$ RH, $\leq 95\%$ RH |
| Open to foot traffic | | 2 hours | 4 hours | 4 hours |
| Installation of floor coverings | Tiles | 6 hours | 12 hours | 12 hours |
| | Resilient Coverings | 24 hours | 24 hours | 24 hours |

* Suitability of Substrates: ... Ideal .. Suitable o Not Suitable

Get in touch:

ROI: T: 01 801 3484 www.kilsaran.ie | **UK:** T: 0161 872 8899 www.kilsaraninternational.co.uk

Place an Order: orders@kilsaran.ie **Customer Service:** csteam@kilsaran.ie

Tech Support: techsupport@kilsaran.ie

